



2-Way Mixes

The following tank mixes have been tested under continuous agitation for physical compatibility with OMAHA® 2 and will mix at recommended rates:

Herbicides

| ANTHEM | Defy | Lector | Quirinus |
|------------------------|---------|------------|------------|
| Atlantis OD + Biopower | Hatra | Most Micro | SPINNAKER |
| Atlantis WG + Biopower | ICONIC | Pitch | Stomp Aqua |
| Crystal | Lantern | Pontos | |

Insecticides

| Clayton Sparta | Karis 10 CS | Sven |
|----------------|-------------|------|
|----------------|-------------|------|

Micro-Nutrients

| Mn S04 | Man X 205 | Omex 15% | Supaman |
|--------|-----------|----------|---------|
|--------|-----------|----------|---------|

3-Way Mixes

The following tank mixes have been tested under continuous agitation for physical compatibility with OMAHA® 2 and will mix at recommended rates:

Herbicides

| Defy + Pontos | Lantern + System 50 |
|---|--|
| Fosburi + Proclus | Pontos + Sunfire |
| Hallmark with Zeon Technology + Lantern | Pontos + System 50 |
| Lantern + Defy | Pontos + Hallmark with Zeon Technology |
| Lantern + Sunfire | |

Incompatible mixes

DO NOT tank mix OMAHA® 2 with Motif

When using tank mixes always follow the statutory conditions of all tank mix partners. Physical compatibility tests check that the products will mix and are suitable for application through a conventional sprayer and may not be approved tank mixes. These tests do not check for any adverse crop effects or the biological efficacy of the individual products when applied in a tank mix. ADAMA Agricultural Solutions UK Ltd gives no warranty and accepts no liability in respect of physical compatibility is and use is at growers own risk. OMAHA[®] 2 is a registered trademark of the ADAMA group. OMAHA[®] 2 contains 40g/L (3.6% w/w) diffufenican and 400g/L (35.6% w/w) pendimethalin. Use plant protection products safely. Always read the label and product information before use. For further product information, including warning phrases and symbols, refer to www.adama.com/uk or call The Technical Helpline on 01635 876 622.